


# Production Requests




## Science Software and Production Requests

Science software is one of the keys to production planning and processing:

- Performs the actual data processing to create desired products.
- Is developed at Science Computing Facilities (SCFs) external to ECS.
- Is embodied in Product Generation Executives (PGEs) when the software is integrated into the ECS production processing environment.
  - PGEs are science software code (e.g., executable programs or shell scripts) that contain the instructions for processing data to create the desired products.


# Production Request Continued



The production request (PR) is another key to production planning and processing. The Production Planner defines ECS science data processing in terms of PRs.

- A PR is an order for data to be produced by the Data Processing Subsystem.
- A single PR may specify several jobs (using the same PGE) that are to be run over a period of time or a single job producing a single set of data.
- PRs may apply to the processing of new data (standard PRs or standing orders) or the reprocessing of existing data (reprocessing PRs).
- Each PR identifies a specific PGE for generating a particular type of product.
  - Some PGEs are dependent on others; i.e., some PGEs require input data that are the output of other PGEs.
  - The planning software will recognize and reject a PR when the PR specifies a PGE that requires data from another PGE that has not yet been specified in a PR.


# Production Request Continued




**The Planning Subsystem performs the following functions:**

- **Uses each PR to generate either one or a series of Data Processing Requests (DPRs).**
  - **Each DPR corresponds to one execution of a single PGE.**
  - **Each DPR contains the information that is needed by the SDP processing function, including PGE-related information.**
- **Checks the availability of the data required for the DPR, either from the Science Data Server (if the data have been previously ingested) or from internal predictions (if the data are expected to arrive in the future).**
- **Determines what data will be included in the DPR output so the system can make predictions concerning the availability of data for subsequent PGEs.**

# Production Request Continued




This figure shows the relationships among the PGEs, PRs, and DPRs as they are accessed through the Production Request Editor GUI.



***Production Request Editor Flow***

# Production Request Continued

---




## Types of Processing

**ECS either accommodates or will accommodate the following four general types of data processing:**

- **Routine Processing**
- **Reprocessing**
- **Ad-Hoc Reprocessing**
- **On-Demand Processing**

# Production Rules




**Provides a template for Instrument Teams to describe the relationship(s) between the PGEs and the input and output data. These specifications cover a variety of issues such as:**

- **Basic Temporal specification**
- **Advanced Temporal specification**
- **Alternate Inputs**
- **Optional Inputs**
- **Minimum/Maximum Number of Granules**
- **Optional DPRs**
- **Intermittent Activation -Every nth DPR is activated; all others skipped**
- **Metadata Checks-based Conditional PGE activation**
- **Metadata Query**
- **Data Day**


# Production Rules Continued

---




- Spatial Query
- Tiling
- Closest Granule
- Orbital Processing
- PGE Exit Conditions

# Basic Temporal



Specify temporal range of inputs that matches temporal range of outputs.




**Production Rule Information Needed for PGE Registration:**

- PGE Schedule Type is "Time Scheduled"
- Boundary and Period of PGE are specified.



# “Time Scheduled” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file:


- **Schedule\_Type = “Time”**
- **Processing\_Boundary = <time boundary on which PGE runs>**
- **Processing\_Period = <interval between PGE runs>**

The Boundary and Period will normally match the expected length and start time of the input data for the PGE. For a PGE that runs on 24 hours worth of data, the Boundary/Period would be set to:

**Processing\_Boundary = “START\_OF\_DAY”**

- **Processing\_Period = “DAYS=1”**

# “Time Scheduled” ODL Files and Parameters (CONT)



The following information needs to be filled out in the ESDT metadata file (for each ESDT that comes from an external source):


- Boundary = <time boundary on which data is collected>
- Period = <interval of data collection>

Data from an external source is periodic data that is not produced by PGEs at the local DAAC. For data that comes in every 2 hours (such as EDOS data):


Processing\_Boundary = “START\_OF\_DAY”

- Processing\_Period = “HOURS=2”

# Advanced Temporal




Specify temporal range of inputs with offsets from expected temporal range of inputs and outputs.



## Production Rule Information Needed for PGE Registration:

- PGE Schedule Type is “Time Scheduled”
- Boundary and Period of PGE are specified as if Basic Temporal.
- Offsets are specified for data that is to be retrieved for another time period.

# “Advanced Temporal” ODL Files and Parameters




The following information needs to be filled out in the PGE metadata file for each input Data Type (PCF Entry) that is to have a timeframe different from the PGEs output:

- **Begin\_Period\_Offset** = <number of seconds to add (+) or subtract (-) from the start collection time when requesting data>
- **End\_Period\_Offset** = <number of seconds to add (+) or subtract (-) from the end collection time when requesting data>


If the PGE runs every hour and desires data for the pervious hour and the current hour (2 granules):

- **Begin\_Period\_Offset** = -3600
- **Processing\_Period** = 0

# Alternate Inputs




Run PGEs with different inputs based on availability or quality of various alternate input data sets.



**Production Rule Information Needed for PGE Registration:**

- Schedule Type and corresponding data.
- Alternate Input Objects for inputs that have alternates.

# “Alternate Input” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file for each Data Type (PCF Entry) that is or has Alternate Inputs:

- **Input\_Type = “Primary”**

(This is the Primary -- First Choice -- Alternate)

- **Input\_Type = “Alternate”**

(This is for every other Alternate)

- **Object = Alternate\_Input**

- **Category = <name of list of alternates; same for every alternate in the list>**

- **Order = <number indicating which alternate comes first, second,...>**


- **Timer = <number of days/hours/seconds to wait for alternate>**

- **WaitFor = <should we wait for this alternate; should be false for all but the last alternate in the list>**


- **Temporal = <does this alternate data type have temporal component>**

- **End Object = Alternate\_Input**

# Optional Inputs




Run PGE with specified inputs if available; otherwise run PGE without them.



**Production Rule Information Needed for PGE Registration:**

- Schedule Type and corresponding data.
- Optional Input Objects for inputs that are optional.

# “Optional Input” ODL Files and Parameters




The following information needs to be filled out in the PGE metadata file for each Data Type (PCF Entry) that is an Optional Input:


- Input\_Type = “Optional”
- Object = Optional\_Input
- Category = <name of list of optionals; same for every alternate in the list>
- Order = <number indicating which optional comes first, second,...>
- Timer = <number of days/hours/seconds to wait for optional>
- Temporal = <does this optional data type have temporal component>
- End Object = Optional\_Input



# Metadata-based PGE Activation




Use metadata of input data set to determine whether a given PGE is to be run.



## Production Rule Information Needed for PGE Registration:

- Schedule Type and corresponding data.
- Metadata Checks Objects for inputs to be checked.
- Metadata Definition objects specifying the type of metadata parameter.


# “Metadata Activation” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file for each input with a metadata check:

- Object = Metadata\_Checks
- Parm\_Name = <name of metadata parameter to check>
- Operator = <operator on parameter value>
- Value = <value to be checked against>
- Database\_Query = <get value from PDPS database; valid values are: NONE, ORBIT NUMBER, PATH NUMBER, TILE ID, START DATA DAY END DATA DAY>
- End Object = Metadata\_Checks


# “Metadata Activation” ODL Files and Parameters (CONT)




The following information needs to be filled out in the ESDT metadata file for each input with a metadata check:

- Object = Metadata\_Definition
- Parm\_Name = <name of metadata parameter to check>
- Container\_Name = <name of container or group that includes metadata parameter>
- Type = <type of parameter (int, float, string)>
- End Object = Metadata\_Definition

# Metadata Query




Use metadata values to further refine the list of inputs acquired for the PGE.



**Production Rule Information Needed for PGE Registration:**

- **Schedule Type and corresponding data.**
- **Metadata Query Objects for inputs to be “refined”.**
- **Metadata Definition objects specifying the type of metadata parameter.**


# “Metadata Query” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file for each input with a metadata query:

- Object = Metadata\_Query
- Parm\_Name = <name of metadata parameter to query against>
- Operator = <operator on parameter value>
- Value = <value to be queried against>
- Database\_Query = <get value from PDPS database; valid values are: NONE, ORBIT NUMBER, PATH NUMBER, TILE ID, START DATA DAY END DATA DAY>
- End Object = Metadata\_Query


# “Metadata Query” ODL Files and Parameters (CONT)



The following information needs to be filled out in the ESDT metadata file for each input with a metadata query:

- Object = Metadata\_Definition
- Parm\_Name = <name of metadata parameter to query>
- Container\_Name = <name of container or group that includes metadata parameter>
- Type = <type of parameter (int, float, string)>
- End Object = Metadata\_Definition


# Intermittent Execution



**Run a PGE every Nth time it is able to be run.**

**Note this is different than the case of running a monthly average once every month (which is covered by the basic temporal rule)**


*run PGE on same data  
set every five days*




## **Production Rule Information Needed for PGE Registration:**

- **None -- this is specified by choices on the Production Request Editor.**

# Special Level 0 Processing Needs (Orbital Processing)



Identify and stage proper input Level 0 data to produce Instrument Team defined Level 1A granules.




**Production Rule Information Needed for PGE Registration:**

- PGE Schedule Type is “Orbit Scheduled”
- Orbit Model ODL file.
- Path Model ODL file (if path mapping desired).



# “Orbit Scheduled” ODL Files and Parameters




The following information needs to be filled out in the PGE metadata file:

- **Schedule\_Type** = “Orbit”
- **Processing\_Boundary** = “Start\_Of\_Orbit”
- **Processing\_Period** = “Orbits=X” <where X is an integer value>


The following information needs to be filled out in the ORBIT metadata file:

- **Platform** = <platform of spacecraft>
- **Orbit\_Start** = <start time of orbit>
- **Orbit\_Number** = <number of orbit>
- **Path\_Number** = <number of path (0-233) matching that orbit>

# Tiling




Identify and stage proper input data to produce Instrument Team defined tiles.



**Production Rule Information Needed for PGE Registration:**

- PGE Schedule Type is “Tile Scheduled”
- Tile ODL file specified.

# “Tile Scheduled” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file:

- **Schedule\_Type** = “Tile”
- **Tile\_Scheme** = <name of tile scheme defined in Tile ODL file>


The following information needs to be filled out in the Tile metadata file:

- **Tile\_Scheme** = <name of tile scheme>


For each tile:

- **Object** = Tile
- **Tile\_ID** = <ID of tile>
- **Tile\_Description** = <description of the tile>
- **Coordinates** = <the coordinates of the four (or more) corners of the tile>

# Data Day




Acquire data for a given Data Day.



**Production Rule Information Needed for PGE Registration:**

- PGE Schedule Type is “Time Scheduled”
- Create PCF Entry for Runtime parameters desired to have Start and End Data Day specified.
- Create Metadata Query object for inputs that are to be requested by Data Day.


# “Data Day” ODL Files and Parameters



The following information needs to be filled out in the PGE metadata file for each input that has to be retrieved by Data Day:

- Object = Metadata\_Query
- Parm\_Name = <Data Day parameter name>
- Operator = “>=“
- Value = “0”
- Database\_Query = “START DATA DAY”
- End Object = Metadata\_Query
- Object = Metadata\_Query
- Parm\_Name = <Data Day parameter name>
- Operator = “<=“
- Value = “0”
- Database\_Query = “END DATA DAY”
- End Object = Metadata\_Query

# **“Data Day” ODL Files and Parameters (CONT)**




The following information needs to be filled out in the PGE metadata file. A PCF entry needs to be created for the runtime parameters that will specify Start and End Data Day values. The following parameter will allow PDPS to populate the runtime parameters with the Start and End Data Days:

**Pge\_Parameter\_Dynamic\_Value = “START DATA DAY”**

or

- **Pge\_Parameter\_Dynamic\_Value = “END DATA DAY”**


# “Data Day” ODL Files and Parameters (CONT)



The following information needs to be filled out in the ESDT metadata file for each input acquired by Data Day:

- Object = Metadata\_Definition
- Parm\_Name = <name of Data Day parameter>
- Container\_Name = “AdditionalAttributes” (because Data Day is in a PSA)
- Type = string
- End Object = Metadata\_Definition

# Final Notes



- Since the implementation of the Production Rules threads is not yet complete, we cannot guarantee that there will not be further refinements of the ODL templates.
- ODL templates can be found online at:
- <http://dmserver.gsfc.nasa.gov/ecsdev/relb/pdps/index.html>
- <http://ecsinfo.hitc.com/iteams/iteams.html>
- Detailed Production Rule Information


Detailed Production Rule Information are covered in depth in publication: MODIS Science Data Processing Software Version 2.0 System Description, SDST-104, dated May 19, 1998.

Test Scenarios for selected Production Rules can be viewed by accessing the SCF at:

`</home/dheroux/DPS/TESTBED/MISR/SSIT/V2/ODL/Scenarios>`




# Science Software and Production Requests



Science software is one of the keys to production planning and processing:

- Performs the actual data processing to create desired products.
- Is developed at Science Computing Facilities (SCFs) external to ECS.
- Is embodied in Product Generation Executives (PGEs) when the software is integrated into the ECS production processing environment.
  - PGEs are science software code (e.g., executable programs or shell scripts) that contain the instructions for processing data to create the desired products.

# Science Software and Production Requests continued




**The production request (PR) is another key to production planning and processing. The Production Planner defines ECS science data processing in terms of PRs.**

- **A PR is an order for data to be produced by the Data Processing Subsystem.**
- **A single PR may specify several jobs (using the same PGE) that are to be run over a period of time or a single job producing a single set of data.**
- **PRs may apply to the processing of new data (standard PRs or standing orders) or the reprocessing of existing data (reprocessing PRs).**


# Science Software and Production Requests continued

---



- **Each PR identifies a specific PGE for generating a particular type of product.**
  - **Some PGEs are dependent on others; i.e., some PGEs require input data that are the output of other PGEs.**
  - **The planning software will recognize and reject a PR when the PR specifies a PGE that requires data from another PGE that has not yet been specified in a PR.**

# Science Software and Production Requests continued





**The Planning Subsystem performs the following functions:**

- **Uses each PR to generate either one or a series of Data Processing Requests (DPRs).**
  - **Each DPR corresponds to one execution of a single PGE.**
  - **Each DPR contains the information that is needed by the SDP processing function, including PGE-related information.**
- **Checks the availability of the data required for the DPR, either from the data server (if the data have been previously ingested) or from internal predictions (if the data are expected to arrive in the future).**
- **Determines what data will be included in the DPR output so the system can make predictions concerning the availability of data for subsequent PGEs.**


**The figure on next slide shows the relationships among the PGEs, PRs, and DPRs as they are accessed through the Production Request Editor GUI.**

# Science Software and Production Requests continued



*Production Request Editor Flow*

# Science Software and Production Requests continued




## Types of Processing

ECS either accommodates or will accommodate the following four general types of data processing:

- Routine Processing
- Reprocessing
- Ad-Hoc Reprocessing
- On-Demand Processing

Routine processing is pre-defined software production processing that is periodic and keyed to data arrival. For example, every day a Production Planner includes in the daily schedule a DPR for generating a particular Level 1A product from the most recent Level 0 data from the applicable satellite instrument


# Science Software and Production Requests continued



**Reprocessing typically involves using a new, improved PGE to process data that had previously been processed with an older version of the PGE. In such cases reprocessing would be a large-scale operation, especially if several years worth of data were to be reprocessed. Consequently, the Production Planner is likely to schedule reprocessing in manageable quantities so the processing resources can accommodate routine and on-demand processing in addition to the reprocessing.**

**In addition, ad-hoc reprocessing could be necessary at any time. For example, if a product fails a quality assurance (QA) check, the same PGE could be run again on the same data set in the hope of creating an acceptable product. Similarly, if processing of a PGE fails for some reason, it might be possible to rerun the PGE and hopefully achieve a successful outcome.**

# Science Software and Production Requests continued




**On-demand processing** is ad-hoc processing initiated by either the Planning Subsystem or an end-user (as opposed to the Production Planner). For example, a researcher using data from the Advanced Spaceborne Thermal Emission and Reflection Radiometer (ASTER) instrument on the Terra satellite may need a particular Level 2 product that has not yet been generated. The ASTER researcher would submit an on-demand request to have the product generated from a Level 1B product stored in the archive.

In the future such on-demand processing requests (OPRs) will be entered from a Client Subsystem tool, passed through the Distributed Information Manager (Data Management Subsystem) and the Data Server to the Planning Subsystem. Currently there is a work-around to the automated process which requires the requester to contact DAAC personnel to make the request. So far ASTER researchers are the only identified external users of automated on-demand processing.



# DPREP




## Introduction

**This section contains information to run DPREP.**


- **DPREP is made up of three PGE's each run separately.**
- **The PGE's are titled Step1 DPREP, Step 2 DPREP and Step 3 DPREP.**
- **The input files normally come from INGEST.**
- **These files are depicted in the three step DPREP process in the diagram depicting the DPREP Processes.**
- **The output files generated from each of the DPREP PGE's contains Ancillary Attitude, and Ephemeris data that becomes new inputs to Instrument PGE's.**

# DPREP Introduction continued




- These Instrument PGE's will then process its satellite data with similar time span files created by DPREP.
- The DPREP registration process for each of the three PGE's creates in the Science Data Server Archive a subscription for each of the DPREP PGE's.
- PGE execution then takes place in the PDPS.
- The SSI&T effort for DPREP PGE's is similar in effort to what would be required to register any other PGE.

# SSI&T Activity for DPREP





- **SSI&T Activity for DPREP**
- **The Level Zero datasets are received in 2 hour chunks.**
- **The file processes diagram depicts the minimal time span allowable for a DPREP run. In a normal operation of DPREP, a twenty four hour time span would be prepared for. This would require additional 2 hour chunks and thus additional files of data would need to be registered.**
- **Before the registration process can take place, a number of files will have to be updated to process a block of data for a particular time period. Therefore, DPREP input files will have to be identified and various templates for the SSI&T process will require annotation.**

# SSI&T Activity for DPREP Cont




- The sections that follow in the Training Manual have been highlighted with notations as to what SSI&T process applies in the preparation of each template and the function required to register each section.
- With a particular function identified, other portions of this manual can be referred to for more detailed procedures to be used to carry out the full SSI&T process.
- Whenever new input files are introduced or updated executables are re-introduced it is wise to first set up the PGE to run from the Command Line. This will determine if what has been introduced will run error free.
- After a successful Command Line run it is advisable then to complete the SSI&T effort to run from the PDPS. Command Line Runs include the use the PCF to run from in the Science Data Server. PDPS runs include ESDT's and ODL files to generate internal PCF's.

# DPREP File Processes



# DPREP Processes



## DPREP Processes and Procedures

Processes and procedures are provided in the following files on an SGI machine used to support SSI&T:

- **DPREP README, HowToCreateDprepTarFile and HowToRunDPREP files** located at **:/usr/ecs/TS1/CUSTOM/data/DPS/**
- **DPREP binary located: :/usr/ecs/TS1/CUSTOM/bin/DPS/**

DPREP consists of three pges each run separately.


**1 The first step is a ksh script called EcDpPrAm1EdosEphAttDPREP\_PGE, which serves as a driver for three executables:**

- **EcDpPrAm1EdosAncillary**
- **EcDpPrAm1EdosEphemerisRepair**
- **EcDpPrAm1ToolkitToHdf**

**2 The second step is EcDpPrAm1FddAttitudeDPREP\_PGE.**

**3 The third step is EcDpPrAm1FddEphemerisDPREP\_PGE.**

# Updating the PDPS Database and Data Server




Integration of Science Software with ECS requires that information about PGEs be made known to the PDPS in its database.

- PDPS needs information to plan, schedule, and run science software.
- PDPS Database and Data Server Tools are accessible from SSIT Manager GUI.

Tools → PDPS Database → PCF ODL Template  
→ SSIT Science Metadata Update  
→ SSIT Opnl Metadata Update

Tools → Data Server → Register Subscription  
→ Insert Static  
→ Insert Test Dynamic  
→ Insert EXE TAR

# Updating the Orbit Model



## Introduction


To determine realtime the latest:

**Orbit Start times, Orbit Period, Path Number and Orbit Number,**

- **PDPS takes in specific information about the orbit of the satellite during initial SSI&T. This information then becomes the basis for predictions of future orbit start times and numbers.**
- **Because this value is accurate within a fraction of a second of time, the satellite may “drift” or a correction to orbit, known as a “burn” may have been applied. Therefore, the satellite Orbit Start Time can get out of sync either +/- with reality.**
- **The consequences are an elapse in time that will affect the Production Request Editor’s ability to find a granule that should match with a DPR, or an incorrect Orbit Time could be passed to the PGE.**
- **The update of Orbit parameters will be done weekly at a specific time with scrips specifically written to extract the new Orbit Parameters from the most recent DPREP output file.**




# Updating the Orbit Model Continued



- These parameters intern will be inserted manually to the ORBIT.ODL file and then the re-registration of the Orbit.ODL file into the PDPS by SSI&T personnel.
- The M&O support Help Desk Team is responsible for knowing when changes to Orbit location have taken place from the Flight Dynamics Systems (FDS).
- A KnowledgeBase with backup procedures will be maintained by M&O for contingencies concerning Orbit Model updates.
- DPREP processing will be the most likely place to experience a failure due to Orbit time sync error encounters. The restoration of Orbit parameters with new values from FDS will most likely be necessary. The following procedures are provided to bring about an updated Orbit Model within ECS.

# Updating the Orbit Model Continued




## Procedures to Update the Orbit Model

Upon receipt of updated orbit parameters: **ORBIT\_NUMBER,**  
**ORBIT\_PERIOD, ORBIT Path Number and**  
**ORBIT\_START Time.**

Proceed with the following steps.

- 1 Telnet or Rlogin to location (ais) system where ODL files are stored. ie;  
“/usr/ecs/OPS/CUSTOM/data/DPS/ODL”**
- 2 Select the ORBIT.odl that is currently being used.**
- 3 Using vi, update the following files with the new parameter values received:**
  - ORBIT\_AM1.odl and/or ORBIT\_EOSAM1.odl if they both are in use.**
- 4 Have someone double check your entries for accuracy before proceeding to the SSIT Manager for registering the new ODL file in the PDPS system.**

# Updating the Orbit Model Continued




**5 For Test Data only; determine the Instrument PGE ODL that will be updated. MISR, MODIS etc.**

- **Using vi, update the corresponding PATHMAP\_Instrument\_.odl file with the new parameter values received.**
- **Ensure that the ABSOLUTE\_PATH and MAPPED\_PATH parameters agree with those in the new ORBIT\_XXXX.odl.**

**6 SSI&T personnel will execute an Orbit Model Update by running a Dummy PGE established for this purpose at each of the DAAC's. Note: A dummy PGE is ran since a normal PGE cannot be re-registered if any DPRs exist in the system.**

**Notify DAAC Operations Supervisor that the Orbit Model has been updated. He will make a log entry of such action taken and may request the old computed values and the new replacement values be provided. The Supervisor will ensure that the orbital change is within several seconds, the expected change and not minutes**


# Updating the PDPS Database with ESDT Metadata



**PDPS needs basic information on every type of file associated with PGEs.**

- **Metadata for the PDPS Database is first prepared in Object Definition Language (ODL), one ODL file for each ESDT.**
- **Determine Science Data Server ShortName for ESDT corresponding to file.**
- **Search ESDT directory for ESDT ODL file. If file exists, there is no need to make another one for this ESDT. The file naming convention is *ESDT\_ShortName.odl*, where *ShortName* is the same name used for the Science Data Server.**
- **If not, copy the ESDT ODL template from configured area to user space.**
- **Add required metadata to ODL file via text editor.**
- **ShortName in ODL file must match ShortName of file itself, ShortName in ESDT descriptor, and ShortName in PGE metadata ODL file.**
- **Copy the ESDT ODL file to the ECS configured area.**

# Updating the PDPS Database with PGE Metadata



**PDPS needs basic information or metadata on the PGE.**


**Order for this Update PGE Metadata Activity: It is recommended that all ESDT metadata ODL files associated with the PGE be prepared and put into the configured area before this procedure is executed.**

**Invoke PCF ODL Template Tool.**

**This tool prompts the user for the following information:**

- **Configuration file - use default ConfigFile path and filename for DAAC**
- **Process Control File - Path and filename of PCF, default path is current**
- **PGE Name - Name of PGE associated with PCF**
- **PGE Version - PGEversion, default needs to be determined if not known**

# Updating the PDPS Database with PGE Metadata (cont.)




Many PCF ODL files can be made on same invocation until user quits.

Program outputs a file with name  
***PGE\_PGEname#PGEversion.tpl***.

Go to full path from which SSIT Manager is run and change this output “.tpl” filename extension to “.odl” or copy template into file with same name and “.odl”.

- Edit ***PGE\_PGEname#PGEversion.odl*** file to add metadata.

# Updating the PDPS Database with PGE Metadata (cont.)



## Process Steps:


- From SSIT Manager select Tools → PDPS Database → SSIT Science Metadata Update.

The program prompts for the following information:

- ConfigFile - use default for path and filename at each DAAC.
- mode - use default of ops.
- PGE name - name of PGE that will be registered (user choice).
- PGE version - PGE version to be registered.
- Quit out of program.

For Version 2 the mode corresponds to ops or TS1 PDPS Database.

# Updating the PDPS Database with Operational Metadata



## Assumption:

All ESDT metadata ODL files associated with the PGE must already be prepared and put into the configured area and the PGE must be registered using the Science Metadata Update Tool.


## Process Steps:

- Invoke the PDPS/SSIT Database Update GUI Tool.
- Select the PGE name and version.
- Select new PGE and Done. PDPS needs basic operational metadata on the PGE to plan resources.
- Select Profile and enter values in fields under Performance Statistics:

Wall clock time	CPU time
Max memory used	Block input ops
Block output ops	Swaps
Page faults	



# Updating PDPS with Operational Metadata




## Process Steps (cont.):

- **Select Resource Requirements and enter values:  
Max disk space used during PGE run.**
- **Select Proc. String. Only one should be listed.  
Number of Processors should be 1.**
- **Select Apply to update the PDPS database.**
- **To start over, use RESET button.**

**The performance statistics collected by running the PGE under EcDpPrRusage will be used to initialize the PDPS database so that the Planning for DPRs can be performed.**


**The actual values entered can be approximate.**

# Placing Dynamic Data Granules on the Science Data Server



- A granule of data is the smallest aggregation of data that is individually managed and archived in the ECS. When products are requested through PDPS, the PGE will be run using the required input data granules acquired from the Science Data Server.
- Dynamic test data granules are delivered with the PGE for input at runtime.
- Insert of dynamic test data is done by a Science Data Server Program.
- DAPs contain MCF templates or samples for output products, not input.
- PGEs, through the SDP Toolkit, generate target MCFs for each data granule produced using the source MCF ODL files delivered with the PGE.
- The target MCFs produced by the PGE are used by the Data Server to insert data products, thus they are called database load ODL files.
- SSI&T will have to create target MCFs (database load ODL files) for input test data granules since they are not produced by a PGE.

# Creating a Target MCF for a Dynamic Data Granule




**Assumption: All ESDT metadata ODL files associated with the PGE must already be prepared and put into the configured area and the PGE must be registered using the SSIT Science Metadata Update Tool.**

**Process Steps to place dynamic data granules on the Science Data Server:**

- **If a source MCF template is not available for the dynamic data granule, then make one by editing a template provided for SSI&T.**
- **Creating a target MCF for dynamic data granule from the source MCF.**
  - **Go to the directory where the source MCF resides.**
  - **Invoke SrcToTargetMCF program from command line.**
  - **Enter source MCF filename (.mcf) and target MCF filename (.met).**
  - **Edit TargetMCFfilename.met file.**
- **For all Data\_Location="PGE" attribute in Source MCF, enter data values.**
- **Date values are provided by Instrument Teams on delivery of the DAP.**
  - **Data granule start date/time and end date/time must be provided.**
- **Save the file.**


# Inserting Dynamic Data Granules to the Science Data Server



## Process Steps for inserting Dynamic Data Granules into the Science Data Server:

- Go to the directory where the dynamic data granule resides.
- From the SSIT Manager GUI → Tools → Data Server → Insert Test Dynamic.
- The Insert Test Dynamic program will be running.
- Enter the following information:
  - ConfigFileName - use default.
  - ESDT ShortName - ESDT ShortName corresponding to data granule.
  - Filename to Insert - Full path & filename of data granule to be inserted.
  - Associated ASCII metadata (target MCF) filename to Insert - same as above filename but with “.met” extension.

# Placing Static Data Granules on the Science Data Server



**Static data granules are those whose temporal locality is static over long periods of time. Examples are calibration files which change only with a new version of the PGE.**

**Static test data granules are delivered with some PGEs.**

**Source MCFs delivered with PGEs are treated as static data granules.**


- **Source MCFs delivered with PGEs can be used from the command line to test a PGE, however an MCF will have to be generated from the SDSRV for use in full PGE integration.**

**Insert of static test data is done by a Data Server Program in SSIT Manager.**

**DAPs contain MCF templates only for output products, not for input files.**

**PGEs, through the SDP Toolkit, generate target MCFs for each data granule produced using the MCF files generated by the SDSRV.**

# Placing Static Data Granules on the Science Data Server (cont.)




**Target MCFs (database load ODL files) are needed to insert all data files, including static data granules, to the Science Data Server.**

**SSI&T will have to create target MCFs (database load ODL files) for static data granules delivered for SSI&T since they are not produced by a PGE.**

**A template for static Metadata ODL files is provided for SSI&T.**

**The static version has parameters unlike those for dynamic data granules.**

# Creating a Metadata ODL File for a Static Data Granule




**Assumption:** All ESDTs associated with the PGE, including either a single ESDT for static type files or an ESDT for each static file, must already be registered. PGE must be registered using Science Metadata Update Tool.

A template metadata ODL file which can be edited is provided for SSI&T by the instrument team.

**Process Steps to place static data granules on the Data Server:**

- **Create a metadata ODL file for a static data granule.**
  - **Go to the directory where the metadata ODL template resides.**
  - **Copy StaticODLmet.tpl to the user work directory as *filename.met*.**
  - **Edit the *filename.met* and enter the following information and save:**
    - ShortName - ESDT ShortName**
    - VersionID - ESDT VersionID**
    - ParameterName - name of static file in InformationContentContainer**
    - ParameterValue - Cn: C = coefficient file, M = MCF; n = 1,2,...**

# Inserting Static Data Granules to the Data Server




## Process Steps for inserting Static Data Granules to the Data Server:

- Go to the directory where the dynamic data granule resides.
- From the SSIT Manager GUI → Tools → Data Server → Insert Static
  - The Insert Static program will be running.
- Enter the following information:
  - Config Filename - use default.
  - Mode - use default mode “ops”
  - ESDT ShortName - ESDT ShortName for data (bucket ESDT).
  - Science Group - Cn: C = coefficient file, M = MCF; n = 1,2,...
  - PGE Name - Name of PGE registered.
  - PGEVersion - PGE version or take default of 1.
  - Filename to Insert - Filename of static data granule to be inserted.
  - Associated ASCII metadata (target MCF) filename to Insert - same as the above filename but with “.met” extension.
- The static granule will be inserted. The program can run again until the user quits.



# Inserting Science Software Executable on the Science Data Server




All science software executables must be inserted on the Data Server to be run by the PDPS. The executable package is called a SSEP or EXE Tar. The steps of this procedure involve three activities:

## Assembling a Science Software Executable Package:

- Make a new directory to hold the contents of the SSEP.
- Copy all files to go into the SSEP into this directory: PGE executables shell scripts, SDP Toolkit message files.
- Use UNIX tar to make the package
- Copy over the Target MCF template to *filename.met*, edit and save:
  - The PGE name is PGEEXE. Enter PGE version and parameter values according to program prompt.
- Select from the SSIT Manager GUI: Tools → Data Server → Insert EXE TAR.
  - Enter PGE Name, SSWVersion, SSEPFileName, ExecFileName

# PGE Planning and Processing




**After the PGE has been linked to the DAAC Version of the SDP Toolkit, all associated ESDT and PGE information has been entered into the PDPS Database, all operational metadata has been entered, and the PGE has been registered, then the PGE is ready to be run in PDPS under AutoSys.**

**The major steps in the PGE Planning and Processing are the following:**

- **Register a subscription for test input and output files (once per ESDT).**
- **Using the Production Request Editor, enter processing information and submit a Production Request.**
- **Using the Planning Workbench, create a new production plan, schedule the processing, activate the plan, and review the planning timeline.**
- **Monitor production under AutoSys.**
- **Using the QA monitor, acquire and view the test output file from the Data Server and examine the Production History File.**

# Registering Subscriptions for Test Input and Output Files




**The Data Subscription Management application is used to manage the receipt of a subscription notification from the Data Server.**

## **Process Steps:**

- **Invoke the Subscription Editor from the SSIT Manager.**
- **From the SSIT Manager GUI →
  - **Tools → Data Server → Register Subscription****
- **Register a subscription for each of the input files and output product files associated with the PGE.**

# Using the Production Request Editor




**The Production Request Editor is a GUI tool which provides the capabilities of submitting a Production Request (PR), looking at production requests in the system, and viewing the Data Production Requests (DPRs) which have been expanded from the original PR.**

**It is invoked from the command line as illustrated in two sections of the accompanying Training Manual 625, titled: Creating a New Production Request and Using the Production Request Editor.**

**Only one PR can be submitted at a time by saving a PR file which is then known to the Planning, Scheduling and Production System. When a PR is submitted, the windows are re-initialized and another PR can be submitted.**

# The Production Request Editor GUI



## TAB DESCRIPTIONS


**Planning** - Displays a list of the four capabilities provided by PR Editor

**PR Edit** - Define and edit Production Requests.


**PR List** - Displays a list of all PRs entered into the system.

**DPR View** - Displays detailed information for a selected DPR.

**DPR List** - Displays all DPRs associated with a selected PR.



# Using the PR Edit GUI




Selecting the PR Edit tab at the top of the main Production Editor GUI.

The following information must be entered on the PR Edit screen:

- **PR Name** - enter as New when PR is being done.
- **Satellite Name** - Name of spacecraft.
- **Instrument Name**- Name of Instrument for which data is being processed.
- **PGE Name** - Name of the PGE registered in the system.
- **PGE Version** - Version of the PGE corresponding to PGE name.
- **Originator** - Name on Instrument Team or data provider.
- **Priority** - Priority to be assigned to this production request.
- **StartDate** - Start date for data coverage.
- **StartTime** - Start time for data coverage.
- **EndDate** - End date for data coverage.
- **EndTime** - End time for data coverage.

# PR Edit GUI



Production Request Editor

File Edit Help

Planning PR Edit PR List DPR View DPR List

Production Request Identification

Origination Date: #N/A

PR Name: New Originator:

Request Definition

Satellite Name: None Priority: 0

Instrument Name: None PGE ...

PGE Name: None PGE Parameters...

PGE Version: None

Duration


Start: Date: Time:

End: Date: Time:

Comment:

Status:

# Using the PR Edit GUI (2)



The PGE information is not entered directly into the PR Edit screen. To enter the PGE information, a pull down GUI is available by selecting “PGE...”. Selecting a PGE from this GUI, enters the related information into the PR Edit screen.



If PGE Parameters are to be examined or changed, a pull down GUI is available by selecting “PGE Parameters...”. The new value may be entered in the override box in this GUI.

Entry of a comment is optional.


When the PR is complete, the “File” tab at the top is selected and a PR filename is entered in the “Save As” box.



# PGE Selection GUI



# PGE Parameter Mapping GUI



PGE Parameter Mappings

PR Name: Day2



Parameter Mapping

Parameter Name	Logical Id	Default Value	Override Value	Desc
SatelliteId	1200	9703381		NON
FirstMissionDay	1201	0		NON
ProcessFirstDayOnly	1202	1		NON
fdF.next.nat.met	1248	1100:1		NON
ProcessEphemeris	1249	on		NON
SatelliteId	1250	107		NON
FirstMissionDay	1251	0		NON
QaWindowSize	1252	5		NON
QaShortGapInterval	1253	0.75		NON
QaLongGapInterval	1254	10.0		NON
QaRedLowAbsolute	1255	-1.0		NON
QaYellowLowAbsolute	1256	-0.5		NON
QaYellowHighAbsolute	1257	0.5		NON
QaRedHighAbsolute	1258	1.0		NON
QaYellowDifference	1259	0.5		NON
QaRedDifference	1260	1.0		NON
QaYellowSampleSD	1261	8.610		NON
QaRedSampleSD	1262	15.544		NON
EulerAngleOrder	1268	3,2,1		NON
attitude.next.nat	1298	1153:1		NON
ProcessAttitude	1299	on		NON


Find

OK Cancel Help

# PR List GUI



# DPR List GUI



Production Request Editor

FileHelp

Planning

PR Edit

PR List

DPR View

DPR List

Production Request:

PR\_TEST1\_v1.0

Filter


Data Processing Requests

DPR Id	PGE Id	PR Name	Data Start Time
CERES_SUB1_v1.00401960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/01/96 00:00:
CERES_SUB1_v1.00402960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/02/96 00:00:
CERES_SUB1_v1.00403960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/03/96 00:00:
CERES_SUB1_v1.00404960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/04/96 00:00:
CERES_SUB1_v1.00405960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/05/96 00:00:
CERES_SUB1_v1.00406960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/06/96 00:00:
CERES_SUB1_v1.00407960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/07/96 00:00:
CERES_SUB1_v1.00408960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/08/96 00:00:
CERES_SUB1_v1.00409960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/09/96 00:00:
CERES_SUB1_v1.00410960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/10/96 00:00:
CERES_SUB1_v1.00411960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/11/96 00:00:
CERES_SUB1_v1.00412960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/12/96 00:00:
CERES_SUB1_v1.00413960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/13/96 00:00:
CERES_SUB1_v1.00414960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/14/96 00:00:
CERES_SUB1_v1.00415960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/15/96 00:00:
CERES_SUB1_v1.00416960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/16/96 00:00:
CERES_SUB1_v1.00417960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/17/96 00:00:
CERES_SUB1_v1.00418960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/18/96 00:00:
CERES_SUB1_v1.00419960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/19/96 00:00:
CERES_SUB1_v1.00420960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/20/96 00:00:
CERES_SUB1_v1.00421960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/21/96 00:00:
CERES_SUB1_v1.00422960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/22/96 00:00:
CERES_SUB1_v1.00423960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/23/96 00:00:
CERES_SUB1_v1.00424960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/24/96 00:00:
CERES_SUB1_v1.00425960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/25/96 00:00:
CERES_SUB1_v1.00426960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/26/96 00:00:
CERES_SUB1_v1.00427960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/27/96 00:00:
CERES_SUB1_v1.00428960000	CERES_SUB1_v1.0	PR_TEST1_v1.0	04/28/96 00:00:

Find

Status:

# DPR View GUI



Production Request Editor

File Help

Planning PR Edit PR List DPR View DPR List

---

Data Processing Request Identification

DPR Name: CERES\_SUB1\_v1.004019600c PR Name: PR\_TEST1\_v1.0

Origination Date: 07/23/96 08:46:37

Originator: jolyon

---

PGE ID: CERES\_SUB1\_v1.0 PGE Parameters...

Data Start Time: 03/31/96 19:00:00 PGE File Mappings...

Data Stop Time: 04/30/96 20:00:00

---

Request Data and Status

Predicted Start

Date: #N/A Time:


Actual Start:

Date: #N/A Time:

Priority: 0 Status: ON\_QUEUE

---

# Creating a New Production Plan




**telnet to (PDPS) p0pls01 or your PLN Host. Use login ID:, PASSWORD:, setenv DISPLAY ....:0.0. setenv <mode>, and source EcCoEnvCsh, then follow instructions from Training Manual, Monitoring Production in PDPS Subsystem.**

**The Planning Workbench is launched to bring up the Planning Workbench GUI. The following information is entered:**

- **File - set to New. Plan Name - User name for plan.**
- **Status is CANDIDATE until plan is activated.**
- **Rollover Time - mm/dd/yy.**
- **Comment - Comments are optional.**
- **Production Request - Select one from the list of all PRs in the system.**
- **Schedule/Unscheduled - select PR and down arrow to schedule PR from unscheduled list and vice versa to unscheduled.**
- **Prioritize - Set priority.**
- **File - use “Save As”, to file under user specified PR name.**
- **Activate - Select to activate plan and enter date/time.**
- **Baseline - Select to create a new baseline plan.**

# Planning Workbench GUI



Planning Workbench

File Options Help

Plan Name: TEST PLAN

Status: CANDIDATE

Baseline

Activate Rollover Time:

Kill

Comments:

This is a production test plan.

Production Requests

Unscheduled:

NAME	PRIORITY
New	1
NewTest	1
PR_CERESS1_v1.0	1
PR_TEST3_v1.0	1
PR_TEST4_v1.0	1


schedule: ▼ unschedule: ▲

Scheduled:

NAME	PRIORITY
PR_TEST1_v1.0	1
PR_TEST2_v1.0	1

Prioritize Refresh

# Review a Production Plan Timeline



**Launch the Planning Workbench and view the production plans.**

**Select the File and Open.**


- **This shows a list of Candidate, Active, and Baseline Production Plans.**

**Select the desired Production Plan to view.**

- **The timeline for the selected Production Plan is displayed.**



# Monitoring Production





**Monitor the PGE executions using AutoSys.**



## **Process Steps:**

- **Launch AutoSys Monitor from the SSIT Manager**
- **Select the DPRs to be displayed in the AutoSys Job Activity Ops Console Window.**
- **Select HostScape or TimeScape or JobScape for different views.**
- **View details of a single DPR.**
- **View the existing Event Report on the selected DPR.**
- **View processing alarms for a DPR.**
- **View job dependencies.**
- **Exit the AutoSys Monitor.**



# AutoSys GUI Control Panel





# AutoXpert HostScape GUI




# AutoXpert Timescape GUI



# AutoXpert JobScape GUI




# Post Processing Activities



Invoke the QA Monitor to view the products and select options.

- **Select Query data and select or query on ESDT and Duration (time range).**
  - **Select Data Granule(s) to check and select Retrieve Data Granule.**
  - **Production History Log files from PGEs run within PDPS.**
  - **Find Data Granule and select Retrieve Production History.**
  - **Examine Production History Log for metadata and other information.**
- **EOSView**
  - **Select Visualize Data.**
  - **Select Attributes to examine metadata in HDF headers.**
  - **Select Table to view data vectors and matrices.**
  - **If an image file is available, select Visualize.**
  - **From the SSIT Manager GUI → Tools → Product Examination → File Comparison → EOSView or IDL.**

# Science Product QA



**Q/A Monitor**

**File** **Help**

**QRU data** **Visualize data**

**Data Types**

- CERX06\_R
- CERX10
- CERX11**
- CERX12
- CERX13
- PGEMISC
- SYN\_MISC

**Find**

**Data Granule Insert Date (mm/dd/yy)**

**Begin** 03 / 23 / 1997

**End** 04 / 23 / 1997

**Query**

**Data Granules:**

Oper	SCF	Auto	Acquisition	Acquisition	Data Granule
QA Flag	QA Flag	QA Flag	Date	Time	FileName
			12/12/96	00:00:00	CERX11_1_AAAa003


**Find**

**Retrieve Data Granule** **Retrieve Prod History** **Update MetaFile**

**Status:**

# Postprocessing and General Investigation

---





## Detection of Science Software Problems and ECS Problems.



- **Examining PGE Log Files**
- 
- **Investigate errors in Production History File.**
- **Use File comparison tools, EOSView and IDL to examine data product problems .**
- **Examine the PDPS Database with the Web Browser.**
- **Submit problems using DDTs.**




# ECS/PDPS Overview



# ECS/PDPS Overview cont.



# Granule Deletion



## Deleting Granules


### Deletion Capability and Features

### Deletion Sequences

### Granule Deletion Procedures:

- Granule Deletion Client Steps
- Run SDSRV Deletion Cleanup Utility
- Delete files from the archive using the STMGT GUI

# Some Reasons for Granule Deletion




## Some Reasons for Granule Deletion

- **The Granule Deletion tool allows operators to delete products on demand**
- **New PGE versions have been created and are used to reprocess large amounts of past data, creating new ESDT versions**
- **lower-level (e.g., Level 2) products are of little or no interest to the science or public user community**
- **One or more granules were found defective and were reprocessed on an individual basis**

# Granule Deletion Capabilities


---



## Deletion Capability and Features

**The Science Data Server has provided an application programming interface (API) for deleting granules from the archive, or from both the archive and inventory since earlier releases, but the Granule Deletion tool adds a front-end command-line utility that provides several ways for selecting granules for deletion.**

# Granule Deletion Sequence




## Deletion Sequence

**The deletion of granules from the archive involves three elements, and therefore actually occurs in stages. Two of the elements are scripts that address the Science Data Server (SDSRV), and the third is a part of the Storage Management (STMGT) Graphical User Interface (GUI).**


**For the first stage, a delete script applies deletion checks to the selected granules, "logically" deleting from the inventory those granules that satisfy the checks. These granules are flagged as 'deleted' and can no longer be accessed, but their inventory entries are not yet removed. The deletion flag consists of a time stamp recording the logical deletion time.**

# Second Stage Sequence



**The second stage is actual deletion from the inventory, which occurs when the operations staff runs the physical deletion script. The script removes all inventory rows for granules that were flagged as 'deleted,' and produces the list of the granule files that are now eligible for deletion from the archive. That list is transferred to the STMGT database. The operations staff controls the lag time between logical deletion and physical deletion. That lag time is entered into the physical deletion script, which deletes only inventory entries for granules that have been logically deleted prior to that time period.**

# Third Stage Sequence




**STMGT provides a GUI screen, as illustrated in Error! Reference source not found., that allows the operator to initiate the removal from the archive of the files listed its deletion table (populated by SDSRV). STMGT creates requests to the archive servers to delete files. The STMGT GUI can be used to look at the state of the deletion requests. Files that are successfully deleted have their associated rows removed from the STMGT database table.**

**Periodically, as sufficient data removal from the archive makes it appropriate, operations may elect to reclaim the tape space and recycle archive tapes. The AMASS software commands (*volcomp*, *volclean*, *volformat*, *volstat*) are used for that purpose**



# STMGT GUI screen for granule deletion from archive



**Batch Delete**

**Granule Deletion Information**

Versioned Data Type	Number of Files
L7IGS.001	2
MOD01.001	25
MOD021KM.001	141
MOD03.001	24
MOD29.001	135
PH.001	205

Select All    Reset    Delete

**Failed Deletion List**

Filename	Versioned Data Type	Server Name	Path	Error Code
----------	---------------------	-------------	------	------------

Close

**Storage Management Control**

File Options Backup Delete

Thursday January 01 10:56:58 AM

Storage Config. Vol Grp Config. Resource Mngmt. Cache Stats.

Configuration Parameter R...

Server Type	# of Servers	Description
SMM	0	SMM Stacker Server
ARCHIVE	3	Archive Server
CACHE MANAGER	4	Cache Management Server
CDROM	0	CDROM Device Server
D3	0	D3 Device Server
DLT	0	DLT Stacker Server
FTP	4	FTP Server
REQUEST MANAGER	1	Request Manager Server

Times to Re-route


Server Name	Status
EcDsStArchiveServerACM4	Up
EcDsStArchiveServerDRP3	Up
EcDsStArchiveServerWKS1	Up

Add Server    Modify Server

Operator Messages

01/11/01 10:56:58 Error purging old database entries


# Using the Granule Deletion Client



**Using the Granule Deletion Client, granules can be selected for deletion several different ways:**

- **ESDT ShortName, Version and granule time coverage**
- **ESDT ShortName, Version and granule insert time range**
- **Separate Input file containing SDSRV Granule IDs**
- **Separate Input file containing ShortName, Version, and Local Granule ID (Logical Granule ID noted in the ticket is referred to in this test as Local Granule ID, which is the name of the parameter as it resides in the database)**

# Client Steps continued



## Granule Deletion Client Steps

**Workspaces are created and each process is carried out for Granule Deletion**

---

**1. Create the following workspaces on the CDE Window manager (xterms created below):**

- **SDSRV**      **5 xterms**
- **STMGT**     **7 xterms**
- **GUIs**       **4 xterms**
- **Database**   **2 xterms**

For Further Steps to carryout Granule Deletion, Please refer to the 625 SSI&T Training Manual Appendix A.